NOISE FUME DUST VENTILATION MONITORING



HAZARD CONTROL SPECIALISTS

ENGINEERING

Control Hire has our own in-house Mechanical and Ventilation engineering team who are experts in our all of our products and applications. Whether it is product advice or fully certified ventilation plans Control Hire has the team that can help.

INSTALLATION

We offer a complete installation and dismantle service for our entire hire fleet. Our expert team can provide turnkey solutions for any of your project requirements.

FILTER SERVICE

Through our on-site filter services, Control Hire offers filter change outs with our equipment, making it easier to protect your workers throughout your project.


ON-SITE SUPPORT

Our technical sales and engineering team are always ready to provide you with on-site support. Control Hire does not just provide you with the latest equipment but also the technical support and service to go along with it.



CONTROLHIRE.COM.AU

NOISE CONTROL WALL



Noise Absorption Side



Control Hire's NOISE CONTROL WALL is the first of its kind, an all in one temporary solution when it comes to noise attenuation.

With performance superior to anything else available in the temporary noise barrier space you can rest assured that you are putting the community and your workers first when it comes to unnecessary noise exposure. The key to noise attenuation is Noise Absorption. Control Hire's Noise Wall achieves an 85% absorption rate or Noise Reduction Coefficient (NRC) which is higher than anything else available in the temporary market today.

The wall traps the soundwaves and dissipates them inside the panel, the absorption is extremely effective at the most sensitive of ranges to the human ear 500Hz, 1000Hz and 2000Hz.



TEMPORARY NOISE WALL


SPECIFICATIONS


NOISE ABSORPTION	85%
Tested	AS ISO 354-2006
Performance	250Hz 81%, 500Hz 92%, 1000Hz 87%, 2000Hz 78%
Assembled Panel Height	2000mm
Assembled Panel Width	2200mm
Assembled Panel Thickness	100mm
Weight	23kg (per section)
Site Conditions	Non-combustible, UV / Water Resistant




Sustainability is important to Control Hire which is why our NOISE CONTROL WALL is made from RECYCLED MATERIALS and the ability to completely recycle the product at the end of its life.

NOISE ABSORPTION - 85% NOISE ABSORPTION









ACOUSTIC NOISE BARRIER

SPECIFICATIONS

Noise Absorption	62%
Height	2000mm
Width	1300mm
Weight	6.3kg
Site Conditions	Fire / Water Resistant



ACOUSTIC MOBILE FOLDING FRAME

SPECIFICATIONS

Noise Absorption	62%
Height	2100mm
Width	2 x 1240mm folded
Weight	36kg
Site Conditions	Fire / Water Resistant



SMALL CUTTING STATION

SPECIFICATIONS

Noise Absorption	62%
Length	2400mm
Width	2400mm
Height	2100mm
Site Conditions	Fire / Water Resistan



LARGE CUTTING STATION

SPECIFICATIONS

Noise Absorption	62%
Length	3250mm
Width	2400mm
Height	2100mm
Site Conditions	Fire / Water Resistant




XL CUTTING STATION

SPECIFICATIONS

Noise Absorption	62%
Length	4800mm
Width	2400mm
Height	2100mm
Site Conditions	Fire / Water Resistant

Temporary construction noise barriers are sound-blocking equipment that protects workers from noise pollution and prevents sound waves from passing directly from construction noise or traffic noise to residences and businesses within the area.

NOISE ABSORPTION - 62% NOISE ABSORPTION





AXIAL FAN 500MM

SPECIFICATIONS

01 2011 10/111	0.110
Airflow	11,880 m³/hr
Motor Size	2.2kW
Plug	240V, 15A
Duct	500mm
Dimensions	510Lx575Wx700H
Weight	69kg



AXIAL FAN 800MM

SPECIFICATIONS

Airflow	30,000m ³ /hr
Motor Size	5.5kW
Plug	415V, 32A
Duct	800mm
Dimensions	700L x 850W x 1000H
Weight	140kg



AXIAL FAN 1000MM

SPECIFICATIONS

Airflow	46,300 m ³ /hr
Motor Size	11.0kW
Plug	415V, 32A
Duct	1220mm
Dimensions	800Lx1106Lx1183H
Weight	221kg



AXIAL FAN 1250MM

SPECIFICATIONS

Airflow	73,700 m ³ /hr
Motor Size	18.5kW
Plug	415V, 32A
Duct	1400mm
Dimensions	800L x 1356L x 1458H
Weight	368kg



CENTRIFUGAL FAN 300MM

SPECIFICATIONS

SI LUII IUNI IUNI	
Airflow	6,000 m ³ /hr
Motor Size	2.0kW
Plug	415V, 32A
Duct	300mm
Dimensions	840Lx715Wx702H
Weight	100kg



CENTRIFUGAL FAN 500MM

SPECIFICATIONS

Airflow	16,000 m ³ /hr
Motor Size	5.5kW
Plug	415V, 32A
Duct	500mm
Dimensions	1560L x 950W x 1450H
Weight	348kg



CENTRIFUGAL FAN 600MM

Airflow	32,000m³/hr
Motor Size	15kW
Plug	415V, 32A
Duct	600mm
Dimensions	1705L x 1250W x 1500H
Weight	500kg







SPECIFICATIONS

Air Flow	6000m³/hr
Fumes	Hot / Flammable
Duct	300mm, up to 90m
Power	415V, 20A



EXHAUST FUME EXTRACTION KIT

SPECIFICATIONS

Airflow	6000m³/hr
Fumes	Diesel Exhaust
Duct	300mm High Temp / 100mm Exhaust Flex, up to 90m
Power	415V, 20A



SPECIFICATIONS

Air Flow	1700 - 3400m³/hr	
Filters	Carbon (Fumes) / HEPA (Dusts)	
Fan	1.5kW	
Power	240V, 10A	



SPECIFICATIONS

Air Flow	5800m³/hr
Filters	Carbon (Fumes) / HEPA (Dusts)
Fan	2.2kW
Power	415V, 20A



MOBILE WELDING **FUME FILTER**

SPECIFICATIONS

Air Flow	1300m³/hr	
ilters	HEPA (Dusts)	
١rm	3m, 160dia	
ower	240V, 10A	
Veight	110kg	



TWIN ARM MOBILE **WELDING FUME FILTER**

Air Flow	2600m³/hr
Filters	HEPA (Dusts)
Arm	2 x 3m, 2 x 160dia
Power	415V, 10A
Weight	180kg



SILICA DUST MONITOR

SPECIFICATIONS

Particle	Respircable Crystaline Silica
Range	1μm - 10μm
Display	RCS mg/m³ time weighted average
TWA	15mins, 1,4,8,12 Hours
Sampling	1-60 seconds
Power	Battery, 240V
Weight	8.2kg



ENVIRONMENTAL DUST MONITOR

SPECIFICATIONS

Particle	Dust
Range	PM1, PM2.5, PM4.25, PM10
Resolution	0.1μg/m³
Data	GPS Cloud Service
Sampling	5 mins
Power	Solar Battery, 240V
Weight	7.0kg



VIBRATION MONITOR

SPECIFICATIONS

Axis	X, Y, Z
Frequency	0.5 - 250 Hz
Velocity	+ 300mm/s
Measurements	PPV, PPA, PVS, VDV, Veff, Vper, KBFmax, KBFTm, Velocity Traces
Data	GPS Cloud Service
Power	Battery, 6 weeks
Weight	260 grams



NOISE MONITOR

SPECIFICATIONS

Measurement	LAF, LAS, LCpeak
Sampling	0.125 seconds / 1 second
Data	Wifi / 4G + Could Service
Power	5VDC (Micro USB) / 24VDC
Weight	1.5kg
Standards	IEC61672-2-2002



ENVIRONMENTAL NOISE MONITOR

SPECIFICATIONS


Measurement	LAeq (optional LCeq, LAFmax or LASmax)
Accuracy	Class 1 (IEC 61672-1)
Sampling	1-60 seconds
Data	GPS Cloud Service
Power	Solar Battery, 240V
Weight	1.15kg



6 IN 1 GAS DETECTOR

Gas	O ₂ , CO ₂ , H ₂ S, NO ₂ , CO, LEL
Range	O ₂ (0-30%vol), LEL (0-100% LEL), CO (0-2000ppm), H ₂ S (0-200ppm), CO ₂ (0- 50,000ppm), NO ₂ (0-20ppm)
Humidity	0%-95%
Temperature	-20°C to 122°C
Battery	12 - 18 hours
Weight	880 grams
Bump Test	Gas Cylinder







FOG LANCE L3

SPECIFICATIONS

Distance	20m
Water Droplet	50 - 60 μm
Controls	Remote
Tilt / Oscillation	30° - 60° / 270
Water Flow	21L/min
Power Plug	3-phase, 32A



ODOUR CANNON V12SO

SPECIFICATIONS

0. 20	
Distance	30m - 50m
Water Droplet	50 - 60 μm
Controls	Remote
Tilt / Oscillation	0° - 52° / 350
Water Flow	4L/min
Power Plug	3-phase, 32/



DUST CANNON V12

SPECIFICATIONS

Distance	35m - 65m
Water Droplet	50 - 60 μm
Controls	Remote
Tilt / Oscillation	18°-40/350
Water Flow	16 - 100L/mir
Power Plug	3-phase, 32A



DUST CANNON V22

SPECIFICATIONS

Distance	70m - 90m
Water Droplet	50 - 60 μm
Controls	Remote
Tilt / Oscillation	18° - 40 / 350°
Water Flow	119 - 350L/min
Power Plug	3-phase, 32A



10KVA GENERATOR

SPECIFICATIONS

OI LOII IOMITIONO	
Appliance	Fog Lance L3
Outlets	2 x 15A, 1 x 20A
Fuel Tank	6.1L Petrol
Power	6.4kW



45KVA GENERATOR

Appliance	V12 Cannon Range
Outlets	2 x 32A, 3 x 15A
Fuel Tank	190L Diesel
Power	33kW



SMALL CUTTING STATION

SPECIFICATIONS

Length	2400mm
Width	2400mm
Height	2100mm
Option	3800m³/hr Air Scrubber
Site Conditions	Fire/Water Resistant



LARGE CUTTING STATION

SPECIFICATIONS

Length	3250mm
Width	2400mm
Height	2100mm
Option	3800m³/hr Air Scrubber
Site Conditions	Fire/Water Resistant



XL CUTTING STATION

SPECIFICATIONS

Length	4800mm
Width	2400mm
Height	2100mm
Option	3800m³/hr Air Scrubber
Site Conditions	Fire/Water Resistant



3400M³/HR AIR SCRUBBER


SPECIFICATIONS

Air Flow	1700 - 3400m³/hr
Filters	HEPA (Dusts)/Carbon (Fumes)
Fan	1.5kW
Power	240V, 10A



5800M³/HR AIR SCRUBBER

Air Flow	5800m³/hr
Filters	HEPA (Dusts)/Carbon (Fumes)
Fan	2.2kW
Power	415V, 20A



























MULTIPLEX



EXPERIENCE

FRESH FOOD & DINING OPPORTUNITIES

CONTROLHIRE

Campbelltown Hospital – Sydney

CONTROLHIRE

CONTROL

NSW

59 POWERS ROAD, SEVEN HILLS
02 8610 5677

VIC

9-11 ORMOND AVENUE, SUNSHINE 03 9966 3794

QLD

21 TRANSPORT STREET, YATALA 07 2802 1779

WE SUPPLY NATIONWIDE

CONTROLHIRE

CONTROLHIRE.COM.AU